



GSC



Gauge Syphon - GSC - GSU - GSUL

Description

The GS series pressure gauge syphons have been designed to protect pressure gauges from the effect of rapid pressure surges and hot pressure fluids. They operate as cooling elements for liquids and gases in pressure measuring devices. An isolation pressure gauge cock is recommended to be installed in combination with gauge syphons.

SYPHONS - 40 Bar rated

Article No.		Size	Price
BSP			
GSC	SS ring syphon	1/2" Male	£87.20
GSU	SS U syphon	1/2" Male	£87.20
GSUL	SS 90 degree U syphon	1/2" Male	£87.20
GSV	SS restrictor type - 100 BAR rated	1/2" Male	£118.50

GSU

GSUL



Materials

Complete stainless steel construction
 Coil AISI 316ti / 1.4571
 Connections AISI 304 / 1.4301



Pressure Gauges for Steam - MAN-100

Pressure gauges have 100 mm diameter and are marked in bar.

Article No.	Pressure Range	Price
5042015	0 - 2.5 BAR	£74.20
5044015	0 - 6 BAR	£74.20
5045015	0 - 10 BAR	£74.20
5046015	0 - 16 BAR	£74.20
5047015	0 - 25 BAR	£74.20
5048015	0 - 40 BAR	£74.20

Materials

Case Stainless steel
 Lens Glass
 Dial Aluminium white
 Pointer Aluminium black
 Measuring system copper alloy



Gauge Cock Isolator Valve - GC-400

Article No.	Type	Price
GC400	Carbon Steel Gauge cock	£79.50
GC400SS	Stainless Steel Gauge cock	£145.60

Materials

Body Steel C22.8 or stainless steel
 Spindle Stainless steel
 Packing PTFE
 Handwheel Plastic



Steam Gauge Assembly Set

Gauge, Isolator & Ring Syphon / U Syphon

Article No. with RING SYPHON	Article No. with U SYPHON	Pressure Range	Size	Price
482841	482998	0 - 6 BAR	1/2" Male	£241.00
482842	482999	0 - 10 BAR	1/2" Male	£241.00
482843	483000	0 - 16 BAR	1/2" Male	£241.00

Typical Instalations

